

Yorkville PLX915XL



Features

- Intrinsic Correction™ tuning and loudspeaker management
- Refined professional appearance looks great in any application
- Best in class audio performance
- Multi - function digital display for control and selection of loudspeaker function including cross-over, EQ, delay and frequency contour
- 2000 watts class D amplifier module
- Deployment in either main PA or floor monitor position
- Dual pole cup mounts

Specifications

| | |
|-----------------|--|
| System Type | 2-way, active loudspeaker |
| Frequency Range | 45 Hz to 20 kHz (-6 dB) 39 Hz to 20 kHz (-10 dB) |
| Coverage Angle | H/V: 90 x 60° (rotatable) Floor Monitor: 50° symmetrical |
| Components | LF: 12.0" / 304.8 mm cone, 3.0" / 76.2 mm voice coil, neodymium magnet HF: 1.4" / 25.4 mm throat compression driver, 2.0" / 50.8 mm voice coil, titanium diaphragm, |
| Sample Rate | 96 kHz and FIR filter |
| SPL | Maximum Output Level (on axis, 3.3' / 1 m): 139 dB |
| Power Rating | Dynamic: 2000 W (LF: 1000 W, HF: 1000 W) Continuous: 1300 W (LF: 920 W, HF: 380 W) |

| | |
|------------------------|---|
| Connectors | 2 x combo XLR/F 3/4" Mic/Line input and Hi-Z/Line input 2 x XLR/M Loop-Thru output, 1 x 3.5 mm. TRS Stereo input 1 x XLR/M Mix output |
| USB | USB 2.0: Host 5 V 500 mA, for USB memory DATA storage/load |
| AC Power Input | Power supply 100 – 200 VAC, 50-60 Hz |
| Amplifier Type | Class-D |
| Enclosure Material | Plywood, durable Polyurea coating, black |
| Dimensions (W × H × D) | 16.1 x 25.4 x 15.5" / 408.9 x 645.2 x 393.7 mm |
| Weight | 47.2 lb / 21.4 kg |