



MODEL : ZS12

Feature

- Deployment in either main PA or floor monitor position.
- Dual pole cup mount (stand and degree down-tilt).
- Best in class audio performance.
- Multi-function digital display for control and selection of loudspeaker functions including cross-over, EQ, delay and frequency contour.
- 2000 watts Class-D amplifier module.
- Factory presets and savable/recallable scenes for commonly-used applications.

Specifications

System

Configuration	2 - way active loudspeaker
Frequency Response	50 Hz – 20 kHz -6dB 45 Hz – 20 kHz -10 dB
Nominal Coverage	75°
Maximum SPL	
Amplifier	130 dB peak Class D
LF HF	Peak 2000 W (12") 400 W (1.4")
Controls	
Power Rotary encoder	3 x Level 2 x selection buttons

VocoPro[®]
BETTER SOUNDING VOCALS

Indicators	Monochrome LED Display 2 x Power LED 3 x Input Signal LED Input A Mic selected LED Input B Hi-Z selected LED Limiter active LED
Connectors	2 x Combo Jack XLR/F 3/4" (mic/Line input and Hi-Z/Line input 2 x XLR(Output),1 x XLR(Mix Output) 1 x Mini Jack (3.5 mm.)
AC Power Input	Power Supply 100 – 240 VAC, 50-60 Hz
AC Power Consumption	100 VAC, 2.1 A - 120 VAC, 1.9 A – 240 VAC, 1.1 A
Dimensions (H x W x D)	712 x 430 x 385 mm (28 x 16.9 x 15.2")
Net Weight	24.4 kg (53.7 lbs)